



OITA UNIVERSITY



OSAKA UNIVERSITY



KYOTO UNIVERSITY



CHIBA
UNIVERSITY



NAGOYA
UNIVERSITY



HOKKAIDO
UNIVERSITY

December 22, 2022

Showa Denko K.K.

Nippon Steel Corporation

Oita University

Osaka University

Kyoto University

Chiba University

Nagoya University

Hokkaido University

**Showa Denko and Nippon Steel, in cooperation with six national universities,
ramps up development of separation/capture technology for low-concentration
CO₂ contained in industrial discharge gas
Early practical application of low-cost and energy-saving CO₂
separation/capture technology will contribute to realizing a carbon neutral
society**

Showa Denko K.K. (President: Hidehito Takahashi, hereafter referred to as SDK), Nippon Steel Corporation (President: Eiji Hashimoto, hereafter referred to as NSC), and six national universities (Oita University, Osaka University, Kyoto University, Chiba University, Nagoya University, and Hokkaido University) have jointly formed a technology development project (hereafter referred to as this Project)*¹. Granted as one of the Green Innovation Fund Projects*² under the New Energy and Industrial Technology Development Organization (NEDO), this Project ramped up development activities in October 2022. This project aims to separate/capture CO₂ efficiently from low-pressure/low-concentration (atmospheric pressure; CO₂ concentration: 10% or lower) discharge gas by using the technologies owned by these two companies and six universities. With the target of achieving an innovatively low cost of 2,000-yen level per ton, this technology is slated for social implementation in the late 2030s. Furthermore, SDK aims to establish a business model that reuses/sells captured CO₂ as raw materials of chemical products.

The period of this Project's R&D activities is nine years from fiscal 2022 to fiscal 2030. Its budget is approx. 8.4 billion yen in total.

Compared with high-pressure gas with a high-concentration of CO₂ discharged from coal fired power generation plants or similar facilities, low-pressure gas with a low-concentration of CO₂ (atmospheric pressure; CO₂ concentration: 10% or lower) discharged from plants such as those in a petrochemical complex or steel mills has big issues such as: (1) separating CO₂ selectively is difficult, and (2) separating processes consume huge amounts of energy. For these reasons, social implementation of CO₂ separation/capture technology has not seen much progress.

This Project has a new challenging development plan that will resolve the issue described above fundamentally by applying a structurally flexible PCP*³, which is totally different from conventional porous materials (such as zeolite and activated carbon), to the process of CO₂ separation/capture from discharge gas with a low pressure and a low concentration of CO₂. While gas molecules are trapped in rigid nano-level pores of zeolite, for structurally flexible PCP, the structure flexibly changes to take in CO₂ molecules to form complexes (inclusion complexes). Its high selectivity for CO₂ is expected to be effective, because only CO₂ molecules, which help form complexes stably, are captured.




Figure 1: CO₂ separation mechanisms of conventional CO₂ separating agent (zeolite) and new agent (structurally flexible PCP)

For conventional porous materials, as the green line in Figure 2 shows, the CO₂ adsorption amount increases and decreases monotonically with respect to the CO₂ pressure. In this case, in order to capture CO₂ adsorbed at a high pressure (point A), the pressure has to be decreased all the way to a low pressure (point B) with a machine such as a vacuum pump. These compression and depression operations consume large energy. On the other hand, for the material to be developed by this Project, as the blue line in Figure 3 shows, the CO₂ adsorption amount changes sharply at a specific pressure. This peculiar behavior is called gate adsorption. When gate adsorption is used, changing pressure slightly between points C and D can advance CO₂ adsorption and desorption. Compared with conventional materials such as zeolite, this material of gate adsorption can reduce theoretically the consumption energy

significantly for separation/capture of CO₂.




Figure 2: Adsorption characteristics of zeolite






Figure 3: Adsorption characteristics of structurally flexible PCP

In order to achieve social implementation of the innovative CO₂ separation technology using this new material, SDK and NSC will combine the separating agent technologies each has originally developed to develop a new revolutionary separating agent that separates CO₂ from discharge gas with a low concentration of CO₂ and that is characterized by low cost and low energy consumption during the separation process. In addition, through the co-creation process of the joint development with Oita University, Osaka University, Kyoto University, Chiba University, Nagoya University, and Hokkaido University, this Project aims at achieving these goals as early as possible.



[Specific activities]

Research and development



Verification of pilot plants




Figure 4: Assignments of development activities in this Project

(1) Improvement of separation agent (SDK, NSC, Oita University, Kyoto University, and Hokkaido University)

Improve the characteristics of separation agents (adsorption pressure and amount).

(2) Process development

(2)-1 Studying forming technology (NSC and Graduate School of Engineering, Osaka University)

Develop a method for forming the separating agent into optimum shapes (development of formative technology)

(2)-2 Gas pretreatment process development (SDK, NSC, and Chiba University)

Each company will develop/design separately the process of removing impurities that promote

separating agent deterioration to separate CO₂ efficiently because components contained in gas vary depending on emission sources.

(2)-3 Basic process development (SDK, NSC, and Nagoya University)

Optimize the processes (shapes of machines and operation conditions) that matches the special CO₂ separation behavior (gate adsorption behavior) of the structurally flexible PCP.

(2)-4 Scale-up of processes (SDK)

Based on the laboratory level basic processes, study the scale-up of processes and design a pilot plant (machines and operation conditions).

(3) Development of separating agent mass production technology (SDK)

Study mass production technology for manufacturing several tens to several hundreds of tons of separating agent (PCP powder and its formed bodies) in the future.


(4) Construction and verification of the pilot plants for CO₂ separation (SDK and NSC)

Verification using petrochemical discharge gas will be conducted at SDK Oita Complex, and verification using discharge gas of steel mills at Oita Area, Kyushu Works, NSC. Both companies will verify the productivities, selectivities, capture rates, lives of separating agents and product qualities, and assess the economic efficiencies of the pre-processes and separating processes.

(5) Verification of the pilot plant of manufacturing chemical products (SDK)

A pilot plant will be constructed at SDK Oita Complex to manufacture chemical products using CO₂ captured from petrochemical and steel mill discharge gas each as a raw material, and verification of manufacturing chemical products using actual gas and assessment of economic efficiency of the plant will be carried out.

[Schedule]



Reference: NEDO's press release document (https://www.nedo.go.jp/news/press/AA5_101541.html)

*1: The formal title of the project is "Development of low-concentration CO₂ separation system using an innovative separating agent/Technology development and demonstration of small- and medium-scale CO₂ separation and capture from factory exhaust gas, etc." It was adopted in May 2022.

*2: The formal title: "Development of Technology for CO₂ Separation, Capture, etc./Green Innovation

Fund Projects"

*3: PCP abbreviation stands for Porous Coordination Polymer.

◆ Contact information for inquiry about this material

- Showa Denko K.K.: Public Relations Group, Brand Communication Department

Tel: +81-3-5470-3235

- Nippon Steel Corporation: Public Relations Center, General Administration Div.

Tel: +81-3-6867-2977

- Oita University: Public Relations Unit, General Affairs Division, Department of General Affairs

Tel: +81-97-554-7376

- Osaka University: Assessment and Publicity Section, General Affairs Division, Graduate School of Engineering

Tel: +81-6-6879-7231, Email: kou-soumu-hyoukakouhou@office.osaka-u.ac.jp

- Kyoto University: iCeMS Communication Design Unit

Tel: +81-75-753-9749, Email: cd@mail2.adm.kyoto-u.ac.jp

- Chiba University: Public Relations Office

Tel: +81-43-290-2018

- Nagoya University: International Communications Office

Tel: +81-52-747-6862, Email: kouho-en@adm.nagoya-u.ac.jp

- Hokkaido University: Shin-ichiro Noro, Professor, Graduate School Faculty of Environmental Earth Science

Tel: +81-11-706-2272, Email: noro@ees.hokudai.ac.jp

Public Relations Division, Department of Public Engagement, Hokkaido University

Tel: +81-11-706-2610, Email: en-press@general.hokudai.ac.jp